





# Sustainable Faecal Sludge Treatment and Reuse: A Case of Faecal Sludge Treatment Plant, Lubhu


By: Reetu Rajbhandari

#### Introduction

Location: Lubhu, Mahalaxmi Municipality, Lalitpur Implementing Partners: ENPHO, and CDD Society (India) Supported by: BORDA, Help for Children Beilngries-Kathmandu, Mahalaxmi Municipality

# **Special Features**

- Prefabricated treatment Modules except Planted Sludge Drying Beds and Planted Gravel Filter.
- Constructed within 45 days
- Footprint: 300 sq. m
- Design Capacity: 6 cum/ week.
- Gravity flow system



#### **Components of Faecal Sludge Treatment Plant(FSTP):**

- Feeding Tank (FT)
  - **Solid Treatment Components:**
  - Biogas Digester (BGD) Stabilization Tank (ST)
  - Planted Sludge Drying Beds (PSDB)
- Liquid Treatment Components:
  - Settler with Integrated Anaerobic Baffle Reactor (ABR) and Anaerobic Filter (AF)
- Planted Gravel Filter (PGF)
- Collection Tank (CT)

# Methodology

- Field observations Interview with operator
- Risk identification to exposure groups at the treatment plant following SSP framework.
- Calculation of monetary value of benefits obtained from treatment plant

## **Overview of Poster**

This poster presents Sustainability study of FSTP through Financial **Assessment and Sanitation Safety** Planning Approach.

### Results

- 1. From the field observation, it has been found that within 21 months of operation:
- 462 m³ of FS has been treated from which 336 m³ of treated water, 48 m³ of compost manure and 631 m<sup>3</sup> of biogas was reclaimed and used.
- Treatment modules are properly maintained and are operational.



- 2. The interview with operator (who is also the farmer using the end products of the treatment plant), imparted that
- Treatment plant has benefitted them with surplus water for irrigation (even during the dry season), compost manure and the sufficient biogas for cooking.
- They do not have to buy the additives (especially minerals) to increase the quality of soil.
- Vegetable production is high compared to past years as they are growing vegetables year round.

- 3. From the SSP assessment,
- No leakages and seepage found - prefabricated and underground components
- Well-trained operator
- Proper use of appropriate personal protective equipment
- Inspection and record keeping of incoming FS before feeding into the treatment plant
- Availability of concern body (SSP team) to
- provide the required technical support and guidance for any susceptible events
- The quality of vegetables grown using the treated water was found with no helminthes indicating safe consumption of the products.



Productio

Compost



4. The calculation of monetary value of benefits obtained showed that about NPR 426,296 could be gained per annum, if treatment plant is fully operational.

	no	ligion
UU		lusion


- Faecal Sludge Management can be merged with resource generation.
- Health risk from exposure to hazardous event can be minimized.
- Zero waste system, as multiple byproducts (biogas, treated water and compost manure) having financial values are produced and are in use.
- FSTP, as such, which closes the sanitation loop, is financially sustainable (benefits: NPR

(Analyzed By)









It represents the time when the abstract was written (December, 2017).

Based on the fiscal year

2073/74.

Considering the density of

loam (1280 kg/m³), total

mass of compost value

QS Test Report / Certificate

Total 262,247

224,000

307,200

Total 688,543